

## CONFIGURATION FLAGS

Here's my listing for IRIX 6.5.x Systems and it's configuration. It shows you which configuration Flags could be disabled when your System is used for default working.

This listing helps to get more free Resources of your Physical Memory. The System will also boot faster than with the standard configuration.

The Flags have to be changed with Root privileges in a Terminal on your System with `chkconfig "Flag" <variable>`. You could list your current configuration with the command `chkconfig` in a Terminal.

Note that you have to reboot your System to enable the changes. Additional information is available by typing `man chkconfig` in a Terminal.

Here's my listing:

Flag	State
====	=====
array	off
autoconfig_ipaddress	off
autofs	on
automount	off
cesag	off
cluster	off
desktop	on
dtlogin	off
esp	on
fcagent	off
fontserver	off
fw_mcserv	off
gated	off
ipaliases	on
ldap	off
lockd	on
lp	on
mediad	on
miser	off
mrouted	off
named	off
nds	off
network	on
netwr_client	off
nfs	on
noiconlogin	off

nostickytmp	off
nsd	on
ntp	off
pmcd	off
pmie	off
privileges	on
proclaim_relayagent	off
proclaim_server	off
proxymngr	off
quickpage	off
rarpd	off
routed	off
rsvpd	off
rtmond	on
rwhod	off
sar	off
savecore	off
sendmail	off
sendmail_cf	off
sesdaemon	off
sgi_apache	off
snetd	off
soundscheme	on
tfxd	off
timed	on
timeslave	off
ts	on
verbose	off
videod	off
visuallogin	on
vswap	off
webface	off
webface_apache	off
windowsystem	on
xdm	on
xlx	on
yp	off
ypmaster	off
ypserv	off